

TAMKO® Glass-Seal®

3-TAB ASPHALT SHINGLES

PRODUCT DATA



MANUFACTURED IN JOPLIN, MO

TAMKO® GLASS-SEAL® self-sealing 3-tab shingles are made with a tough TAMKO fiberglass mat, coated on both sides with a thick layer of weathering-grade asphalt and surfaced with ceramic granules.

USES

For application to roof decks with inclines of not less than 2 inches per foot. For slopes between 2 inches and 4 inches per foot, refer to wrapper instructions.

ADVANTAGES

- 20-year limited warranty, 3-year FULL START, limited transferability, winds up to 60 MPH.
- Class A fire resistance.

CERTIFICATIONS/REPORTS

Listed by UL for:
Class A Fire Rating
Wind Resistance
ASTM D 3462

Tested in compliance with:


UL 790/ASTM E 108, Class A
ASTM D 3161, Type I, Class A
UL 2390/ASTM D 6381, Class H (150 mph)
ASTM D 7158, Class H (150 mph)

COLORS

- Antique Slate
- Rustic Black
- Rustic Cedar
- Rustic Hickory
- Tweed Blend
- Weathered Wood
- White

PRODUCT DATA*

Shingle size 12" x 36"
Exposure 5"
Coverage per Sales Square 100 sq.ft.
Shingles per Sales Square 80
Bundles per Sales Square 3



*All values stated as nominal



TAMKO
BUILDING PRODUCTS

TAMKO Logo, Roofer Logo, TAMKO Glass-Seal® and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

CAUTION: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known" human carcinogens by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

Central District	220 West 4th St.	Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr.	Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St.	Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp.	Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave.	Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

For information regarding or a copy of TAMKO's limited warranty, contact your local TAMKO representative, visit us online at tamko.com, or call us at 800-641-4691.