

TAMKO

BUILDING PRODUCTS



TW WINDOW & DOOR FLASH

FLASHING MEMBRANE

Window and door openings are particularly prone to water infiltration. For this reason, it makes sense to apply added protection in these vulnerable areas. TAMKO® offers the ideal solution with its TW Window & Door Flash product. This easy-to-apply membrane is designed to help seal window and door perimeters and keep water outside of the building envelope.

TW WINDOW & DOOR FLASH

FLASHING MEMBRANE



TW Window & Door Flash is a flexible, self-adhering rubberized asphalt sheet membrane with a white polymer film surface that resists U.V. degradation for up to 180 days and has a removable treated release film on the adhesive side. TW Window & Door Flash is well suited for sealing window and door perimeters.

Available in 4", 6" and 9" wide rolls. Nominal thickness is 25 mil.

OTHER TAMKO® WATERPROOFING OPTIONS



TW FLASH-N-WRAP®-25

is a flexible self-adhering rubberized asphalt sheet membrane with a tough reflective aluminum film surface that resists U.V. degradation for up to 180 days and has a removable treated release film on the adhesive side. TW Flash-N-Wrap-25 is well suited for sealing window and door openings.

Available in 4", 6", 9", 12" and 18" wide rolls. Nominal thickness is 25 mil.



TW FLASH-N-WRAP®-40

is a flexible self-adhering rubberized asphalt sheet membrane with a tough reflective aluminum film surface that resists U.V. degradation for up to 180 days and has a removable treated release film on the adhesive side. TW Flash-N-Wrap-40 is well suited for cavity wall construction as a moisture and air barrier membrane.

Available in 4", 6", 9", 12", 18" and 36" wide rolls. Nominal thickness is 40 mil.



TW MOISTURE WRAP

is a flexible self-adhering rubberized asphalt sheet membrane with a clear polymer film on the surface that resists U.V. degradation for up to 30 days and has a removable silicone-treated release film on the adhesive side. TW Moisture Wrap is well suited for application in cavity wall construction, the sealing of window and door perimeters and the sealing of wall joints, corners and other terminations.

Available in 4", 6", 9", 12", 18", 24", 36" and 39-3/8" wide rolls. Nominal thickness is 40 mil.



BUILDING PRODUCTS FOR THE PROFESSIONAL

TAMKO[®]
BUILDING PRODUCTS

©2008 TAMKO Building Products, Inc.
TAMKO and TW Flash-N-Wrap are registered
trademarks of TAMKO Building Products, Inc.

This product is covered by a 5-year limited warranty. To obtain a copy of TAMKO's limited warranty, visit us online at tamko.com or call us at 1-800-641-4691. Information included in this product sheet was current at the time of printing. To obtain a copy of the most current version of this product sheet, visit us online at tamko.com or call us at 1-800-641-4691.

P.O. Box 1404 Joplin, MO 64802
1-800-641-4691
tamko.com

