



Application Instructions for • HERITAGE® VINTAGE® 12" x 12" HIP AND RIDGE FIBERGLASS SHINGLES



Apply shingles up to a hip or ridge from both sides of the roof before finishing the intersection. To facilitate finishing, adjust the last few courses so that the ridge capping will adequately cover the top courses of shingles equally on both sides of the ridge.

To apply the capping, bend each shingle along the centerline so that it will extend an equal distance on each side of the hip or ridge. Chalk lines may assist in proper alignment. In cold weather, warm the shingle until it is pliable before bending.

Apply the shingles with a 5 in. exposure, beginning at the bottom of the hip or from the end of the ridge opposite the direction of the prevailing winds. See Figure 1. Secure each shingle as illustrated in Figure 2, with one fastener on each side, 5-1/2 in. back from the exposed end and 1 in. up from the edge. Length of fastener for hip and ridge shingles should be 1/4 in. longer than recommended for shingles.

In high wind areas, it may be advisable, at the discretion of the roofing contractor, to use a spot of sealant to minimize blow off problems. It is recommended that a 2-layer application of Heritage Vintage 12"x 12" Hip and Ridge be applied to all Heritage Vintage roofs to enhance the overall appearance.

When the second layer is applied, offset this layer by 1/4 in. to create a "shadow" effect. See Figure 3.



The length of the fastener should be long enough to penetrate through the roofing material and 3/4 in. into the wood decking or completely through approved plywood.

IMPORTANT - READ CAREFULLY BEFORE OPENING BUNDLE

In this paragraph "You" and "Your" refer to the installer of the shingles and the owner of the building on which these shingles will be installed. This is a legally binding agreement between You and TAMKO Building Products, Inc. ("TAMKO"). By opening this bundle You agree: (a) to install the shingles strictly in accordance with the instructions printed on this wrapper; and (b) leaks and other roofing defects resulting from failure to follow the manufacturers installation instructions printed on this wrapper are not covered by the limited warranty that is also printed on this wrapper, or any other warranty, including, but not limited to (except where prohibited by law) implied warranties of MERCHANTABILITY and FITNESS FOR USE.

©2008 TAMKO Building Products, Inc.
 TAMKO Logo, Heritage® and TAMKO® are registered trademarks of TAMKO Building Products, Inc.

Visit Our Web Site at
tamko.com

| | | |
|--------------------|--|--------------|
| Central District | 220 West 4th St., Joplin, MO 64801 | 800-641-4691 |
| Northeast District | 4500 Tamko Dr., Frederick, MD 21701 | 800-368-2055 |
| Southeast District | 2300 35th St., Tuscaloosa, AL 35401 | 800-228-2656 |
| Southwest District | 7910 S. Central Exp., Dallas, TX 75216 | 800-443-1834 |
| Western District | 5300 East 43rd Ave., Denver, CO 80216 | 800-530-8868 |

07/08