

TAMKO® TW-105 FLASHING

Self-Adhering Sheet Waterproofing Membrane

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

The surface to receive TW-105 Flashing must be clean, dry and have a smooth finish. **Note: Flash or Fill any gaps in or between substrates greater than 1/2" with appropriate material such as metal flashing, non-shrink grout, backer rod, etc.**

Priming-

Priming is required for all applications. Prime with TAMKO TWP-1 Primer*** or TWP-2 Water-Based Primer as appropriate for the surface to be primed.

***WARNINGS AND HAZARDS

TWP-1 Primer contains combustible solvents. Avoid exposure to sparks, open flame, heat, and other forms of ignition. Use in well-ventilated areas. Avoid breathing vapors. Refer to SDS for detailed product information and warnings. SDS information is available online at tamko.com, or by calling TAMKO's Technical Services Department at 1-800-641-4691.

FLASHING APPLICATION

Install TW-105 Flashing at wall/floor intersections and other transition locations. TW-105 Flashing must not be exposed to ponding water. Refer to Construction Detail on second page of application instructions or the "TAMKO Waterproofing Construction Detail TW-14", which is available online at tamko.com. Apply when temperature is 35° F or above during the entire installation. Side laps must be 2-1/2", and end laps must be 5" and lapped the direction of water flow. Apply TAMKO TWM-1 Mastic at all terminating edges. Membrane must not be left exposed to sunlight for more than 30 days.

Warning: Failure to use adequate pressure at terminating edges will result in poor seal, potential leaks and may affect coverage under the limited warranty which can be found at tamko.com or by calling 800-641-4691. The use of mastic is not a substitute for a good seal.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691. INFORMATION INCLUDED IN THE APPLICATION INSTRUCTIONS WAS CURRENT AT TIME OF PRINTING. TO OBTAIN A COPY OF THE MOST CURRENT VERSION OF THESE APPLICATION INSTRUCTIONS, VISIT US ONLINE AT TAMKO.COM OR CALL US AT 800-641-4691.

MEMBRANE PROTECTION

Protection of TW-105 on vertical and horizontal surfaces is required immediately after installation with an appropriate protection course as designated in the Protection Course for Use with TAMKO TW-60 Waterproofing Membrane section of the TAMKO TW-60 Self-Adhering Sheet Waterproofing Membrane Application Instructions. For balcony and breezeway installations, use of protection course is not required.

Information included in the application instructions was current at time of printing. To obtain a copy of the most current version of the application instructions, visit us online at tamko.com or call us at 800-641-4691.

WARNING

This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov/product.

SDS information is available from TAMKO's website at tamko.com, or by calling TAMKO's Technical Services Department at 1-800-641-4691.



APPROPRIATE FALL PROTECTION METHODS MUST BE USED WHEN INSTALLING PRODUCTS. Use Caution, Wrapper and Product may be slippery.



P.O. Box 1404 • Joplin, MO 64802-1404 • 1-800-641-4691 • tamko.com