

STORMFIGHTER F L E X



Featuring TAMKO's all-new proprietary polymer technology ForceFX™



Introducing the all-weather performance shingle with the **FLEX**ibility to help withstand impact, high winds, rain, and freezing temperatures.

UP TO 35% INCREASED TEAR RESISTANCE*

SUPERIOR HANDLING AND SEALING IN COLD WEATHER

ENHANCED
GRANULE ADHESION

* When compared to industry standard ASTM D3462 based on testing conducted Jan-Sept 2023.

160 MPH WIND WARRANTY

Highest wind warranty IR shingle







[†] See StormFighter FLEX's full High Wind Application Instructions for all requirements and restrictions.

INSTALL DOWN TO 250

Install in freezing temperatures







IMPACT RATED











‡ Stormfighter FLEX™ 3 and 4 shingles are classified by UL for compliance with UL 2218 Class 3 or Class 4 impact resistance.

CONTRACTORS WHO TRIED STORMFIGHTER FLEX™ SAID:

"It's going to be a... game-changer for the industry." "It's a 10 we'll sell the heck out of it." "I don't think anyone has anything close to it." "You were the best — you took [my typical shingle] and beat it up pretty good."

	STORMFIGHTER FLEX4	STORMFIGHTER FLEX3	OTHER BRANDS POLYMER MODIFIED SHINGLES
UL TESTED IMPACT RATING	Class 4	Class 3	Class 3 or Class 4
HIGH WIND WARRANTY MPH	160 MPH	160 MPH	130 MPH
LOWEST INSTALL TEMPERATURE PER MANUFACTURER	25º F	25º F	45º F
SUPERIOR FLEXIBILITY	V	V	_
REINFORCED NAILING ZONE	V	V	_
ADVANCED SHINGLE SEALANT	V	V	_

TAMKO BUILDING PRODUCTS LLC 1-800-641-4691 tamko.com





INDUSTRY LEADING WARRANTY, PERFORMANCE, & TECHNOLOGY

STORMFIGHTER FLEX™ PREMIUM COLOR OPTIONS

















Prior to making your final color selection, TAMKO recommends viewing an actual roof installation. See **tamko.com/colorselection** for complete details.

StormFighter FLEX™ shingles meet the following classifications

UL Listed for: Class A Fire Resistance

UL Classified:Wind Resistance
Impact Resistance
ASTM D3462 and ICC-ES
Acceptance Criteria AC438

Tested in Compliance with: UL 790/ASTM E 108, Class A ASTM D3161, Class F ASTM D7158, Class H

UL 2218 Class 3' Impact Resistance UL 2218 Class 4' Impact Resistance ASTM D3462

ICC-ES Acceptance Criteria AC438

UL Evaluation Reports:

UL Evaluation Report ER2919-01
UL Evaluation Report ER2919-02

Florida Building Code Product Approval FL 18355 FL 35321

Miami-Dade County Product Control Approved

Olde English Pewter is listed by the Cool Roof Rating Council* (CRRC)

†Stormfighter FLEX™ 3 and 4 shingles are classified by UL for compliance with UL 2218 Class 3 or Class 4 impact resistance.

