

TAMKO® SA BASE

SELF-ADHERING SBS MODIFIED BASE SHEET

MANUFACTURED IN JOPLIN, MO

PRODUCT DATA

DESCRIPTION

TAMKO® SA BASE is a flexible, fiberglass reinforced, self-adhering, SBS modified asphalt membrane with a polymer film on the surface and a removable split release film on the adhesive side.

- Fiberglass reinforcement.
- Self-adhering.
- TAMKO® SA Roofing System 15-year Limited Warranty and Arbitration Agreement.

USES: TAMKO® SA BASE is used in TAMKO® SA roofing system, when used in conjunction with TAMKO® SA CAP Sheet. SA BASE can be used as a roofing base sheet that can be applied by removing the split release film from the adhesive side and pressing the base sheet's self-adhesive back surface into place. Alternate nail application is available online at tamko.com.

LOW SLOPE AND COMMERCIAL PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG LOW-SLOPE AND COMMERCIAL PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

TECHNICAL INFORMATION

UL Classified Base Sheet

Independently tested for compliance with: ASTM D1970

UL Evaluation Reports: UL ER3225-01

Florida Building Code Approved FL17491

Miami Dade County Product Control Approved

PRODUCT DATA

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

Reinforcement Fiberglass Mat

Polymer Type Styrene-Butadiene-Styrene (SBS)

Roll Size[†] 65' 10" x 39-3/8"

Roll Contains^{††} 2.05 Squares

[†]Subject to manufacturing variation

^{††}When applied according to application instructions



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica. Crystalline silica has been classified as "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a 'probable human carcinogen'. Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com