

TAMKO® FOUNDATION COATING

PRODUCT DATA



PRODUCT NUMBER
 30001270 - 5 GAL - Green Cove Springs FL
 30001640 - 5 GAL - Columbus KS

USES

High-quality non-fibered, below grade moisture protection. Formulated from select penetrating pure asphalts and fast setting petroleum solvents to create a corrosion resistant brush consistency liquid. It penetrates pores and seals resisting cracks and moisture migration.

Used primarily for below-grade moisture protection and damp-proofing for exterior masonry, concrete and metal surfaces. Seals out moisture and prevents corrosion. Not intended for use where a hydrostatic head of water or other severe conditions exist.

ADVANTAGES

Foundations - A two coat application is recommended allowing the first coat to dry 24 hours. Apply material from footing to grade level, working and coating all crevices and pores. Uniformity is important. Do not leave thin or bare spots. Outside temperature must be 50°F and rising.

2 Coat Application:
 1 gallon covers 75 - 100 sq. ft. per coat

PRODUCT DATA*

TYPICAL PHYSICAL PROPERTIES*	MIN	MAX
Total solids (non-volatiles), %	65	75
Volatiles, %	25	35
Flash point, °F	100	- -
VOC, grams/litre	- -	300
Viscosity, Stormer/100 rev. @77°F, seconds	20	40

*All values stated as nominal

For Technical Services call 1-800-641-4691

Visit our Web Site at tamko.com



TAMKO Logo, Roofer Logo and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

CAUTION: The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. This product should not be heated or burned using a direct flame device. Take precautions to prevent breathing and contact with skin.

Central District	220 West 4th St.	Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr.	Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St.	Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp.	Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave.	Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.