

TAMKO® NO.15 UL Asphalt Saturated Organic Felt

PRODUCT DATA

Manufactured in Tuscaloosa, AL

TAMKO® NO. 15 UL felt features a tough TAMKO organic felt (non-perforated) that is saturated with asphalt.



USES

Accepted for use as an underlayment felt to be applied over the deck prior to the installation of TAMKO asphalt shingles.


CERTIFICATIONS

U.L. Built-Up Type 15 Label
ASTM D 226, Type I

PRODUCT DATA*

Roll Dimensions	144' X 36"
Coverage per roll	4 Squares
Laying Lines	2", 4", 17"

*All values stated as nominal



THIS PRODUCT IS SOLD "AS IS" WITHOUT WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Visit our Web Site at tamko.com



TAMKO
BUILDING PRODUCTS

TAMKO Logo, Roofer Logo and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

CAUTION: This product contains wood dust. Wood dust has been classified as a "known" human carcinogen by the International Agency for Research on Cancer and the National Toxicology Program. This product contains asphalt. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

Central District	220 West 4th St.	Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr.	Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St.	Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp.	Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave.	Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.