

# TAM-PRO® Q-20 PREMIUM SBS FLASHING CEMENT

PRODUCT DATA

## DESCRIPTION

A heavy bodied SBS polymer modified trowel grade wet/dry formula asphaltic cement. Combining select refined asphalt, prime solvents, wet surface additives, SBS (styrene-butadiene-styrene) rubberized polymers and extra strength interlocking fibers. This material is precisely blended into a smooth thixotropic, high performance material. Elastomeric properties promote expansion and contraction with the SBS modified bitumen membrane. **100% ASBESTOS FREE!**

## USES

This premium SBS flashing cement is ideal for use in adhering SBS modified bitumen membrane flashings and laps. May also be used for fiberglass built-up roof system flashing applications.

## APPLICATION

Surface to be treated must be free of dirt, dust, oil, etc. Prime all metal, concrete, and masonry surfaces with TAM-PRO 813 Quick Dry Asphalt Primer prior to use. Apply TAM-PRO Premium SBS Flashing Cement directly from the container with a trowel or knife at a rate of 1/8 inch per 100 square feet. Also, mechanical fasteners should be used to fasten the Modified Bitumen membrane per generally accepted roofing application on vertical or sloped flashings.

**Precautions:** For cold weather application, store at room temperature for 24 hours prior to use. Not for use with APP (Atactic Polypropylene) or membranes which have a plastic or polypropylene backing.

## APPLICABLE STANDARDS

ASTM D 4586 Type I Standard Specification for Asphalt Roof Cement. ASTM D 3409 Standard Test Method for Adhesion of Asphalt Roof Cement to Damp, Wet, or Underwater Surfaces. Miami-Dade County Product Control Approved NOA 08-0423.16 Expiration Date 07/24/13



## PRODUCT NUMBER

30001285 – 3 GAL – Green Cove Springs FL  
 30001286 – (WG) 3 GAL – Green Cove Springs FL  
 30001287 – 5 GAL – Green Cove Springs FL  
 30001288 – (WG) 5 GAL – Green Cove Springs FL  
 30001289 – (SEMI) 5 GAL – Green Cove Springs FL  
 30001648 – 3 GAL – Columbus KS  
 30001649 – (WG) 3 GAL – Columbus KS  
 30001650 – 5 GAL – Columbus KS  
 30001651 – (WG) 5 GAL – Columbus KS

**CAUTION:** This product contains crystalline silica. Crystalline silica has been classified as a “known” human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified “extracts of steam and air-refined bitumens” (cutback asphalt) as “possibly carcinogenic to humans.” The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.

## TYPICAL PHYSICAL PROPERTIES\*

	MIN	MAX	METHOD
Total solids (non-volatile), %	70	80	D 4586
Volatiles, %	30	35	D 4586
Flash Point, F	105	--	D 92
Low Temperature Flexibility			Meets D 4586
VOC, grams/litre	--	300	

\*All values stated as nominal

For Technical Services call 800-641-4691.

Central District	220 West 4th Street, Joplin, Missouri 64801	800-641-4691
Northeast District	4500 Tamko Drive, Frederick, Maryland 21701	800-368-2055
Southeast District	2300 35th Street, Tuscaloosa, Alabama 35401	800-228-2656
Southwest District	7910 South Central Expressway, Dallas, Texas 75216	800-443-1834
Western District	5300 East 43rd Avenue, Denver, Colorado 80216	800-530-8868

TAMKO® and TAM-PRO® are registered trademarks of TAMKO Building Products, Inc.

©2012 TAMKO Building Products, Inc.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

tamko.com

