

# TAMKO® TAM- FELT®

## ASPHALT SATURATED ORGANIC FELT

## PRODUCT DATA



MANUFACTURED IN GREEN COVE SPRINGS, FL

**IMPORTANT SAFETY INFORMATION:** Use personal fall protection devices when working on a roof. Personal fall protection devices, safety glasses and hearing protection must always be used when applying Tam-Felt underlayment. Moisture, frost or debris will decrease the traction when walking on Tam-Felt underlayment. **Applicator safety is of utmost importance.**

**TAM-FELT** is a TAMKO organic felt (non-perforated) that is saturated with asphalt. Tam-Felt serves as an alternative to ASTM D226 Type I & II saturated felt, and has been tested by a third-party laboratory in accordance with ICC-ES AC188 and the physical properties of ASTM D226.

**USES:** For use as an underlayment prior to installation of asphalt shingles.

- 36" x 144' coverage 4.08 squares
- 432 square feet per roll
- Laying Lines at 2", 4" and 17"

**NOTICE: THIS PRODUCT IS SOLD "AS IS" AND WITHOUT WARRANTY OF ANY KIND, EXPRESS, IMPLIED OR STATUTORY, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

**CERTIFICATIONS**

UL Classified as a Prepared Roofing Accessory

UL Evaluation Reports: UL ER10827-01

Florida Building Code Approved: FL 12328

**LIMITATIONS**

- Underlayment must not be applied to wet or frosty surfaces.
- Underlayment must not be applied to unclean or contaminated surfaces.
- Underlayment must not come into contact with products containing coal-tar pitch.

**PRODUCT DATA†**

	<b>4.08 Square Roll</b>
Roll Dimensions	36" x 144'
Roll Coverage††	408 sq. ft. (± 3.94 sq. ft.)
Roll Contains	432 sq. ft. (± 3.99 sq. ft.)
Rolls Per Pallet	30
Pallet Size	36" x 45"

† All values stated as nominal.

†† When applied according to instructions.

**CAUTION:** This product contains wood dust. Wood dust has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

TAMKO Logo and TAMKO® are registered trademarks and Tam-Felt is a trademark of TAMKO® Building Products, Inc.

