

TAMKO® 12-1/4 x 12 HIP & RIDGE

ROOFING ACCESSORY

MANUFACTURED IN JOPLIN, MO

PRODUCT DATA

DESCRIPTION

12-1/4 x 12 HIP & RIDGE features a fiberglass mat coated on both sides with weathering-grade asphalt and surfaced with mineral granules. Covered by the TAMKO Limited Warranty and Arbitration Agreement for the TAMKO® shingles covering the field of the roof.

- Each shingle is perforated into 3 pieces for separation prior to application.
- Self-sealing strip of asphalt.

USES: Hip & Ridge forms a cap along various angles of the roof.

- For use with TAMKO® shingle products.

SHINGLES BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG SHINGLES WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. THIS PRODUCT IS COVERED BY THE TAMKO LIMITED WARRANTY FOR THE TAMKO SHINGLES COVERING THE FIELD OF THE ROOF. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY FOR TAMKO SHINGLES COVERING THE FIELD OF THE ROOF AT TAMKO.COM OR BY CALLING 1-800-641-4691.

COLORS

- Antique Slate
- Antique Wood
- Autumn Brown
- Black Sage
- Black Walnut
- Cabin Wood Brown
- Cedar Wood
- Desert Sand
- Driftwood
- Glacier White*
- Grey Mist
- Harvest Gold
- Mountain Slate
- Natural Timber
- Olde English Pewter
- Oxford Grey
- Painted Desert
- Rustic Black
- Rustic Brown
- Rustic Cedar
- Rustic Evergreen
- Rustic Hickory
- Rustic Redwood
- Rustic Slate
- Shadow Grey
- Thunderstorm Grey
- Weathered Wood

TECHNICAL INFORMATION



*Glacier White is ENERGY STAR qualified.



*Glacier White is rated by the Cool Roof Rating Council.

UL Listed for Class A Fire Rating:	UL 790/ASTM E108, Class A
UL Classified for Wind Resistance:	ASTM D3161, Class F
UL Classified in accordance with:	ASTM D3462 and ICC-ES Acceptance Criteria AC438
UL Evaluation Reports:	UL ER2919-01 and UL ER2919-02
Florida Building Code Approved:	FL18355
Miami-Dade County Florida Approved:	NOA 14-1001.08 Expiration Date: 01/08/2019

PRODUCT DATA

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

Shingle sizes†	12-1/4" x 36"
Perforated Shingle size	12-1/4" x 12"
Exposure	5-1/8"
Perforated Shingles per 100 lineal feet	234
Bundles per 100 lineal feet	3

†Subject to manufacturing variation



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com