COOLRIDGE®

SECTIONAL RIDGE VENT WITH INTERNAL FILTER

DESCRIPTION

	COOLRIDGE® is an injection-molded polypropylene sectional ridge vent with internal filter.
	 18 square inches of net free area per linear foot. 25-40 year Limited Warranty and Arbitration Agreement from TAMKO (depending on shingle installed). Internal supports in nail line area provide compression resistance for nailing. Embossed nail line and 1/2" nail zone area with clear space underneath help facilitate proper nailing. Exterior baffles and internal "sinewave"-shaped baffles help keep rain and snow out. Male/female connection between pieces helps protect seams from leaks. Vent holes are only 1/8" wide to help prevent insect infiltration. Drain holes every 4" in exterior baffle to prevent water build-up. Internal filter provides greater protection against wind-driven rain and snow infiltration. USES: Used to properly ventilate attic space when used in conjunction with soffit vents. For slopes above 12 inches per foot, call for technical support at 1-800-641-4691.
	WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.
REQUIREMENTS	
TECHNICAL INFORMATION	 Must be used with an equal or greater amount of soffit ventilation. Minimum 3/12 roof pitch (up to 16/12). Use with standard 12" wide cap shingles. Use provided 2-1/2" nails to assure penetration of at least 3/4" into decking.
	Florida Building Code Approved: FL4103
PRODUCT DATA	Meets or exceeds requirements of Texas Dept. of Insurance RV-28
Information included in this product data sheet was current	Width [†] 14-3/4"

at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or

call us at 800-641-4691.

Width [†]	14-3/4"
Height ⁺	13/16"
Length [†]	48" long
12 Pieces per bundle	48 ft. per package
Color	Black

[†]Subject to manufacturing variation



P.O. Box 1404 Joplin, MO 64802-1404 800-641-4691 tamko.com



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. <u>The TAMKO Safety Data Sheet (SDS)</u> is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance**.