

HERITAGE® DESIGNER RIDGE

HIGH PROFILE RIDGE

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

HERITAGE® DESIGNER RIDGE shingles are a high profile ridge cap constructed with SBS Modified Bitumen Technology. Up to 1/2" thicker the standard Heritage® Hip & Ridge.

USES: To form a cap along various angles of the roof. For use with Heritage® and Heritage® Premium Shingles.

- Self-sealing adhesive
- Complementary colors for TAMKO Heritage® Shingles†

SHINGLES BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG SHINGLES WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

COLORS

- Antique Slate
- Autumn Brown
- Black Walnut
- Desert Sand
- Glacier White
- Harvest Gold
- Mountain Slate
- Natural Timber
- Old English Pewter
- Oxford Grey
- Painted Desert
- Rustic Black
- Rustic Brown
- Rustic Cedar
- Rustic Evergreen
- Rustic Hickory
- Rustic Redwood
- Rustic Slate
- Thunderstorm Grey
- Weathered Wood

TECHNICAL INFORMATION

UL Listed for Class A Fire Rating:	UL 790 Class A Fire Resistance
UL Classified for Wind Resistance:	ASTM D3161, Class F for wind resistance

PRODUCT DATA

Shingle sizes†	8" × 11-1/2"
	10" × 11-1/2"
Exposure	8"
Linear ft. per carton	20
Shingles per 100 linear ft.	150
Shingles per carton	30
Cartons per pallet	42

† Not all colors and sizes may be available in your area.
Contact your TAMKO Sales Representative for complete color and size availability.

WARNING: Use of polyurethane foam insulation applied directly to the underside of a roof deck may cause premature degradation or failure of this asphalt roofing product. We are investigating compatibility of polyurethane foams with our asphalt building products. Chemical incompatibility, off-gassing after application and excess heat during and after application of polyurethane foams may affect the performance of asphalt and modified asphalt building products and metal fasteners used with those products.



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com