

MOISTURE GUARD®

ICE & RAIN UNDERLAYMENT

MANUFACTURED IN JOPLIN, MO

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

MOISTURE GUARD® is a self-adhering SBS modified bitumen sheet membrane for prevention of water penetration caused by wind-blown rain or ice damming.

- Self-adhering SBS modified rubberized asphalt.
- Mineral surfacing.
- Fiberglass mat.
- Split treated release film.
- Seldedge release tape.
- 5-Year Limited Warranty and Arbitration Agreement.

USES: For use under wood shake, asphalt and composite shingles at eaves, rakes and valleys, around chimneys and skylights, and in other areas of the roof where windblown rain and ice damming is a possibility. It is not recommended for use under metal roofings.*

UNDERLAYMENTS PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY ON MOISTURE GUARD, TW METAL & TILE, TW UNDERLAYMENT, SYNTHETIC GUARD PLUS, AND SYNTHETIC GUARD. THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

*Use TAMKO's TW Metal & Tile Underlayment or TW Underlayment for metal roofing applications.

TECHNICAL INFORMATION

UL Classified as a Prepared Roofing Accessory

UL Classified in accordance with: ASTM D1970

Florida Building Code Approved: FL12328

Miami Dade County Approved: NOA 17-0531.01 Expiration Date: 07/05/2022

LIMITATIONS

- Underlayment must not be applied to wet or frosty surfaces.
- Underlayment should not be applied to unclean or contaminated surfaces.
- Underlayment must not come into contact with products containing coal-tar pitch.
- Must be applied at temperatures of 40 °F and higher.
- Once applied, underlayment must not be left exposed beyond 90 days.

PRODUCT DATA

	0.87 Sales Square Roll	1.74 Sales Square Roll
Roll Dimensions†	36" x 32'3"	36" x 64'6"
Roll Coverage††	87.34 sq. ft. (± 1.52 sq. ft.)	174.69 sq. ft. (±1.52 sq. ft.)
Roll Contains	96.75 sq. ft. (± 1.68 sq. ft.)	193.5 sq. ft. (±1.68 sq. ft.)
Thickness†	55 mils	55 mils
Rolls Per Pallet	49	25

†Subject to manufacturing variation

††When applied according to instructions



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\)](http://tamko.com/sds) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

TAMKO
BUILDING PRODUCTS

P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com