

TAMKO® SA CAP

SELF-ADHERING SBS MODIFIED CAP SHEET

MANUFACTURED IN JOPLIN, MO

PRODUCT DATA

DESCRIPTION

TAMKO® SA CAP is a lightweight, flexible dual-coated SBS-modified cap sheet constructed with a non-woven polyester mat, self-adhering adhesive, a split release film on the adhesive side and is surfaced with ceramic granules for protection from ultraviolet degradation.

- Flexible.
- Puncture and tear resistant.
- TAMKO® SA Roofing System 15-year Limited Warranty and Arbitration Agreement.
- Available in a variety of colors.

USES: Roofing membrane and flashing membrane for low-sloped applications and flashing details. This cap sheet is applied by removing the split release film from the adhesive side and pressing the membrane's self-adhesive back surface into place.

LOW SLOPE AND COMMERCIAL PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG LOW-SLOPE AND COMMERCIAL PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

COLORS

- Buff
- Rustic Hickory
- Glacier White
- Shadow Grey
- Rustic Black
- Weathered Wood
- Rustic Cedar

TECHNICAL INFORMATION

UL Classified Membrane for Roofing Systems

Independently tested for compliance with: ASTM D6164, Type I

UL Evaluation Report: UL ER3225-01

Florida Building Code Approved FL17491

Miami Dade County Product Control Approved

PRODUCT DATA

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

| | |
|-----------------|---------------------------------|
| Reinforcement | Polyester Mat |
| Polymer Type | Styrene-Butadiene-Styrene (SBS) |
| Roll Size† | 39-3/8" x 33-1/2' |
| Roll Contains†† | .99 Square |

†Subject to manufacturing variation

††When applied according to application instructions



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\)](http://tamko.com/sds) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica. Crystalline silica has been classified as "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogens". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com