

TAMKO® SA CAP

Self-Adhering SBS Modified Cap Sheet

PRODUCT DATA

DESCRIPTION

TAMKO SA CAP is a lightweight, highly flexible dual-coated SBS modified cap sheet constructed with a non-woven polyester mat, self-adhering adhesive, a split removable release film on the adhesive side, and is surfaced with ceramic granules for protection from ultraviolet degradation.

USES

Roofing membrane and flashing membrane for low-sloped residential applications and flashing details. This cap sheet is easily applied by removing the split release film from the adhesive side and pressing the membrane's self-adhesive back surface into place.

ADVANTAGES

- Lightweight
- Flexible
- Puncture and tear resistant
- Meets ASTM D 6164, Type 1, G
- Self-adhering
- Split release film
- 15-year limited material warranty when applied in accordance with TAMKO application instructions together with TAMKO SA Base in a roofing system.
- Available in a variety of colored granule finishes
- Minimal dead load weight

CERTIFICATIONS

U.L. Classified Membrane for Class C Roofing Systems

LIMITATIONS

- Membrane should not be applied to damp, frosty or contaminated surfaces.
- Membrane should not come into contact with products containing coal-tar pitch.
- Membrane should not be used in applications with PVC roofing or other products that contain tackifiers, plasticizers or processing oils.
- Membrane should be applied when air, substrate and membrane temperatures are above 45° F.
- Deck should be built with a nominal 1/2" exterior wood decking.

PRODUCT DATA¹

Reinforcement	Polyester Mat
Asphalt Modifier	SBS
Roll Size	39.375" x 33.52'
Coverage	1 square

WHEN APPLIED ACCORDING TO INSTRUCTIONS,
COVERS 99.99 SQUARE FEET
ROLL CONTAINS 111.30 SQUARE FEET

¹Subject to manufacturing variation



SA CAP COLORS

- Weathered Wood
- Rustic Cedar
- Rustic Black
- Buff
- Glacier White
- Shadow Grey
- Rustic Hickory

CAUTION: This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as know or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

TAMKO[®]
BUILDING PRODUCTS