

TAMKO® TW-105 FLASHING

SELF-ADHERING SHEET WATERPROOFING MEMBRANE

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

DESCRIPTION

TAMKO® TW-105 Flashing is a self-adhering rubberized asphalt sheet membrane with a polymer film on the surface and removable split release film on the adhesive side.

- Self-adhered
- Split release film
- Available in Winter and Summer Grade formulation
- 5-year Limited Warranty and Arbitration Agreement

USES: Used for balcony and breezeway detail. Install at wall/floor intersections and other transition locations.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

PRODUCT DATA

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

Roll Size	12" × 40'
Roll Width	12"
One Roll Contains	40 sq. ft.
Rolls Per Pallet	70, 2 rolls per carton
Cartons Per Pallet	35
Asphalt Modifier	Styrenic Block Copolymer
Product Thickness [†]	105 mil thickness

[†]Subject to manufacturing variation

ACCESSORY PRODUCTS

- TAMKO TWP-1 Quick Dry Waterproofing Primer 5 gallon size
- TAMKO TWP-2 Water Based Waterproofing Primer 5 gallon size
- TAMKO TWM-1 Mastic 10.5 oz tube, 1 quart tube or 3 gallon
- TAMKO TW-60 Self Adhering Sheet Waterproofing Membrane



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com

WARNING: This product contains crystalline silica. Crystalline silica has been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.