

TW FLASH-N-WRAP® PRO

SELF-ADHERING FLASHING MEMBRANE

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TW FLASH-N-WRAP® PRO is a self-adhering rubberized asphalt flashing membrane with a white polymer surface film and a removable treated release film on the adhesive side.

- Adheres to cast-in-place concrete, pre-cast concrete, masonry block, exterior gypsum sheathing, plywood, OSB, DensGlass®, EPS insulation, vinyl or metal surfaces.
- Available in factory pre-cut widths of 4", 6", and 9".
- Individually wrapped factory pre-cut widths with point-of-purchase (POP) labels are available in 4", 6", and 9" roll sizes.
- White film surface for UV resistance.
- 5-year Limited Warranty and Arbitration Agreement.

USES: TW FLASH-N-WRAP® PRO is used to seal window and door perimeters and keep water outside of the building envelope.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY FOR MANY PRODUCTS, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

LIMITATIONS

- White polymer film surface resists UV degradation up to 180 days, however TAMKO recommends covering this material as soon as possible for ultimate product performance as severe weather to exposed product may affect performance.
- Membrane must not come in contact with products containing coal-tar pitch.
- Membrane must be applied when air, substrate and membrane temperatures are above 40°F.
- Not intended for use on roofs or prolonged exposure to temperatures above 200 °F.

PRODUCT DATA

| Roll Width | Roll Size | Linear Feet per Carton | Rolls per Carton |
|-------------------------|--------------------------|------------------------|------------------|
| Individually Wrapped 4" | 4" × 100' | 900' | 9 |
| Individually Wrapped 6" | 6" × 100' | 600' | 6 |
| Individually Wrapped 9" | 9" × 100' | 400' | 4 |
| Non-wrapped 4" | 4" × 100' | 900' | 9 |
| Non-wrapped 6" | 6" × 100' | 600' | 6 |
| Non-wrapped 9" | 9" × 100' | 400' | 4 |
| Surfacing | White Polymer Film | | |
| Asphalt Modifier | Styrenic Block Copolymer | | |
| Product Thickness† | 25 mil | | |

†Subject to manufacturing variation



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica. Crystalline silica has been classified as a "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.