

TW MOISTURE WRAP

MOISTURE/AIR BARRIER MEMBRANE

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TW MOISTURE WRAP is a self-adhering rubberized asphalt sheet membrane with a clear polymer film on the surface.

- Treated release film for installation and handling
- Available in factory pre-cut widths of 4", 6", 9", 12", 18", 24", and 36" rolls
- Adheres to cast-in-place concrete, precast concrete, concrete masonry block, exterior gypsum sheathing, plywood, OSB, DensGlass®, EPS insulation, felt and foil-faced polyisocyanurate foam insulation, wood, vinyl or metal surfaces
- 5-year Limited Warranty and Arbitration Agreement

USES: TW Moisture Wrap can be used as an above-grade moisture/air barrier for application in cavity wall construction, the sealing of window and door perimeters and sealing of wall joints, corners and other terminations.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

LIMITATIONS

- Membrane or primer must not be applied to damp, frosty or contaminated surfaces
- Membrane or primer must not be left exposed to sunlight for more than 30 days. For applications requiring longer exposure before covering, use TW Window & Door Flash, TW Flash-N-Wrap® 25, or TW Flash-N-Wrap® 40. TAMKO recommends covering this material as soon as possible for ultimate product performance as severe weather to exposed product may affect performance
- Membrane must not come into contact with products containing coal-tar pitch.
- Membrane must be applied when air, substrate and membrane temperatures are above 40°F
- Not designed for use in ponding areas
- Not intended for use on roofs or prolonged exposure to temperatures above 200 ° F

PRODUCT DATA

Roll Width [†]	Roll Size [†]	Coverage per Ctn. [†]	Rolls per Ctn.
4"	4"×75'	225 sq. ft.	9
6"	6"×75'	225 sq. ft.	6
9"	9"×75'	225 sq. ft.	4
12"	12"×75'	225 sq. ft.	3
18"	18"×75'	225 sq. ft.	2
24"	24"×75'	150 sq. ft.	1
36"	36"×75'	225 sq. ft.	1
Ind. Wrap 4"	4"×75'	225 sq. ft.	9
Ind. Wrap 6"	6"×75'	225 sq. ft.	6
Ind. Wrap 9"	9"×75'	225 sq. ft.	4
Surfacing	Polymer		
Asphalt Modifier	Styrenic Block Copolymer		

[†]Subject to manufacturing variation



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\)](http://tamko.com/sds) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

TAMKO[®]
BUILDING PRODUCTS

P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com

TW MOISTURE WRAP

MOISTURE/AIR BARRIER MEMBRANE

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

TYPICAL PHYSICAL PROPERTIES

Test	ASTM Standards	Minimum Physical Properties
Peel Adhesion (lbf/in.)	ASTM D3330	
Plywood (APA Exposure 1)		6.5



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com