

TAMKO® TW SEAM TAPE

SELF-ADHERING ROOF DECK SEAM TAPE

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TAMKO® TW SEAM TAPE is a flexible, self-adhering SBS modified bitumen roof deck seam tape with a polymer film on the surface and a removable treated release film on the adhesive side.

- Textured, skid resistant surface
- Adheres to exterior gypsum sheathing, plywood, OSB, DensGlass®, felt-faced and foil-faced polyisocyanurate foam insulation, wood or metal surfaces.
- Treated release film
- 5-year Limited Warranty and Arbitration Agreement

USES: For use as a roof deck seam tape to cover all joints and seams. Provides secondary protection against water penetration at deck seams and joints.

BUILDING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG BUILDING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY FOR MANY PRODUCTS, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

LIMITATIONS

- Tape or primer must not be applied to damp, frosty, or contaminated surfaces.
- Tape must be applied to inclines of not less than 2 inches per foot.
- Must be applied at temperatures of 40°F and higher.
- Tape must not be exposed to UV rays for more than 120 days.
- Tested for High Temperature Resistance up to 240°F.**

**See TAMKO Technical Notice dated May 4, 2018 for testing information. Available at tamko.com

TECHNICAL INFORMATION

UL Prepared Roofing Accessory

UL Classified in accordance with: ASTM D1970

PRODUCT DATA

Rolls per Carton	9
Roll Coverage†	61 linear ft.
Roll Dimensions††	4" x 61'
Thickness††	40 mils
Cartons per Pallet	30

† When applied according to application instructions

†† Subject to manufacturing variation

WARNING: Use of this product in an assembly that includes polyurethane foam insulation (including without limitation an application directly to the underside of a roof deck or within a wall assembly) may cause premature degradation or failure of this product. We are investigating compatibility of polyurethane foams with our asphalt building products. Chemical incompatibility, off-gassing after application and excess heat during and after application of polyurethane foams may affect the performance of asphalt and modified asphalt building products and metal fasteners used with those products.



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds.](http://tamko.com/sds) Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica. Crystalline silica has been classified as "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product contains asphalt. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com