

TW-THRU WALL FLASHING

SELF-ADHERING SHEET MEMBRANE

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TW-THRU WALL FLASHING is a flexible self-adhering sheet membrane consisting of a self-adhering rubberized asphalt and an 8-mil polymer film as the top surface.

- Rubberized asphalt sheet has high adhesive quality
- Treated release film for ease of installation
- Available in factory precut widths of 12", 18", 24" and 36" rolls
- 5-Year Limited Warranty and Arbitration Agreement

USES: Used as an in-wall flashing membrane for use with concrete, masonry, gypsum, felt-faced and foil-faced polyisocyanurate foam insulation or wood construction.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

LIMITATIONS

- TW-THRU WALL FLASHING cannot be left exposed to sunlight longer than 60 days
- Membrane must be applied when air, substrate and membrane temperatures are above 40°F
- Membrane should not be brought into contact with products containing coal-tar pitch
- Not intended for use on roofs or prolonged exposure to temperatures above 200°F

TYPICAL PHYSICAL PROPERTIES

Roll Widths	Roll Size	Coverage per Ctn.	Rolls per Ctn.
12"	12" × 75'	225 sq. ft.	3
18"	18" × 75'	225 sq. ft.	2
24"	24" × 75'	150 sq. ft.	1
36"	36" × 75'	225 sq. ft.	1
Film Surfacing	8 mil Cross Laminated High Density Polyethylene Film		
Asphalt Modifier	Styrenic Block Copolymer		
Product Thickness [†]	40 mil		

[†]Subject to manufacturing variation



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\)](http://tamko.com/sds) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica. Crystalline silica has been classified as "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

TAMKO[®]
BUILDING PRODUCTS

P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com