

TAMKO® TWM-1 MASTIC

RUBBERIZED BITUMEN MASTIC

MANUFACTURED IN COLUMBUS, KS

PRODUCT DATA

DESCRIPTION

TWM-1 MASTIC is a high quality, trowel grade, rubberized bitumen mastic. TWM-1 dries to a pliable seal allowing for minor expansion and contraction.

- Available in 10.5 oz. tubes, quart tubes, and 3 gallon buckets
- Applied with a trowel or caulking gun
- 5-Year Limited Warranty and Arbitration Agreement

USES: For multiple uses, including finishing the edge of seams, overlaps, patches and terminations of properly sealed TAMKO waterproofing membranes. This product is also suitable for use in roof flashing application and contains additives for use in wet and dry conditions.

WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

APPLICATION

Apply with a trowel or caulking gun. When applied with a caulking gun, the bead should be troweled to a thickness of 1/8" and a width of 1/2" to 1" and worked into all terminations.

COVERAGE RATES

Side Laps:	900 lineal feet per gallon
End Laps:	600 lineal feet per gallon

LIMITATIONS

- Not suitable for use as a waterproofing concrete/masonry sealer.
- When used to terminate the edges of a TAMKO Waterproofing membrane, the use of TWM-1 Mastic is not a substitute for the seal of the waterproofing membrane itself.

TYPICAL PHYSICAL PROPERTIES

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

Color	Black
VOC	280 grams per liter
Flash Point (COC)	>100°F
Packaging	3 gallon pails, 29 or 10.5 oz tubes



P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com

WARNING: This product contains crystalline silica. Crystalline silica has been classified as a "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified "extracts of steam and air-refined bitumens" (cutback asphalt) as "possibly carcinogenic to humans." The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.