

# TWP-1 QUICK DRY PRIMER

## QUICK DRY WATERPROOFING PRIMER

## PRODUCT DATA

### DESCRIPTION

**TWP-1 QUICK DRY PRIMER** is a high quality rubberized primer formulated for below-grade waterproofing.

- Available in 5 gallon buckets.
- Applied with a roller or spray equipment.
- 5-Year Limited Warranty and Arbitration Agreement.

**USES:** To promote a powerful bond to asphalt, concrete, masonry, DensGlass® sheathing, OSB, plywood, and metal surfaces.

- Features a red tint to make it easier to identify areas that have been primed.
- Ideal for use in preparing surfaces that receive a sheet of waterproofing membrane.

**WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.**

### APPLICATION

Apply with a long nap roller or spray equipment at the rate of 250 to 300 square feet per gallon. Allow to cure until the surface is tacky, but will not transfer when touched. Primer should be allowed to dry a minimum of 1 hour and a maximum of 8 hours. Do not thin with organic solvents.

### LIMITATIONS

- TWP-1 Quick Dry Primer must not be used on or come into contact with EPS/XPS or ICF surfaces.

### TYPICAL PHYSICAL PROPERTIES

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

Solids Content	38% by weight
Tack Free Time	30 min. @ 75°F
VOC	Less than 450 grams/litre†
Flash Point	<68°F
Packaging	5 gallon pails

†This primer does not meet the VOC requirements in the following states California, Delaware, Maryland, New Jersey, New York, Pennsylvania, Virginia, Maine, and the District of Columbia.



P.O. Box 1404  
Joplin, MO 64802-1404  
800-641-4691  
[tamko.com](http://tamko.com)



**IMPORTANT SAFETY INFORMATION:** Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds.](http://tamko.com/sds) Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**