

TAM-PRO® 801 PLASTIC ROOF CEMENT PRODUCT DATA

DESCRIPTION

A versatile roofing mastic that contains a precise blend of select asphalts, petroleum solvents, tough reinforcing fibers, and special additives that enhance spreadability. Dries to form a durable, but pliable, seal that allows for minor expansion and contraction. Acid and alkali resistant, it bonds to all clean surfaces except coal tar-based materials. **100% ASBESTOS FREE!**

USES

Flashing construction and other detail roofing work such as tie-offs or shingle securement. Provides excellent waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.

APPLICATION

Apply with a trowel or knife. One gallon covers 12.5 sq.ft. to an 1/8" thickness.

APPLICABLE STANDARDS

ASTM D 4586 Type I Standard Specification for Asphalt Roof Cement
Miami-Dade County Product Control Approved
NOA 08-0423.16 Expiration Date 07/24/13

CAUTION: This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified "extracts of steam and air-refined bitumens" (cutback asphalt) as "possibly carcinogenic to humans." The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.



PRODUCT NUMBER

30001220 – 3 GAL – Green Cove Springs FL
30001221 – (WG) 3 GAL – Green Cove Springs FL
30001222 – 5 GAL – Green Cove Springs FL
30001223 – (WG) 5 GAL – Green Cove Springs FL
30001224 – (SEMI) 5 GAL – Green Cove Springs FL

30001631 – 3 GAL – Columbus KS
30001614 – (WG) 3 GAL – Columbus KS
30001615 – 5 GAL – Columbus KS
30001616 – (WG) 5 GAL – Columbus KS

TYPICAL PHYSICAL PROPERTIES*

	MIN	MAX	METHOD
Total solids (non-volatile), %	75	85	D 4586
Volatiles, %	15	25	D 4586
Flash Point, F	100	--	D 92
Asphalt, %	35	65	D 4
Viscosity, Cone Penetration @ 77 F, 1/10 mm	265	295	
VOC, grams/litre	--	300	

*All values stated as nominal

For Technical Services call 800-641-4691.

Central District	220 West 4th Street, Joplin, Missouri 64801	800-641-4691
Northeast District	4500 Tamko Drive, Frederick, Maryland 21701	800-368-2055
Southeast District	2300 35th Street, Tuscaloosa, Alabama 35401	800-228-2656
Southwest District	7910 South Central Expressway, Dallas, Texas 75216	800-443-1834
Western District	5300 East 43rd Avenue, Denver, Colorado 80216	800-530-8868

TAMKO® and TAM-PRO® are registered trademarks of TAMKO Building Products, Inc.

©2012 TAMKO Building Products, Inc.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

tamko.com

