

# TAMKO® NO. 30 ASTM SHAKE UNDERLAYMENT

## ASPHALT SATURATED ORGANIC FELT

MANUFACTURED IN JOPLIN, MO

## PRODUCT DATA

### DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

**TAMKO® NO. 30 ASTM SHAKE UNDERLAYMENT ASPHALT SATURATED ORGANIC FELT** is a non-perforated organic felt that is saturated with asphalt.

**USES:** To be applied over the roof deck prior to the installation of wood shake or wood shingles to help prevent premature failure of the shingles and provide a secondary layer of moisture protection.

**NOTICE: THIS PRODUCT IS SOLD "AS IS" AND WITHOUT WARRANTY OF ANY KIND. ALL WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.**

### TECHNICAL INFORMATION

UL Prepared Roofing Accessory

UL Classified in Accordance With: ASTM D226, Type II

### PRODUCT DATA

Roll Dimensions† 18" × 120'

Roll Coverage†† 160 SQ. FT.

Laying Lines 8", 10"

†Subject to manufacturing variation

††When applied according to application instructions



P.O. Box 97  
Galena, KS 66739-0097  
800-641-4691  
[tamko.com](http://tamko.com)



**IMPORTANT SAFETY INFORMATION:** Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at [tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

**WARNING:** This product contains wood dust. Wood dust has been classified as a "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by the IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalations or dermal hazard during application and/or removal. However, forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product.