

TAMKO® WET OR DRY SURFACE PLASTIC ROOF CEMENT

PRODUCT DATA

A heavy-bodied all-weather roofing mastic containing special modifiers to enhance bonding to damp surfaces. Formulated from select asphalts, penetrating petroleum solvents, and tough reinforcing fibers. Dries to form a durable, but pliable, seal that allows for minor expansion and contraction. Bonds to all damp clean surfaces except coal tar based materials.

100% ASBESTOS FREE- GUARANTEED!



PRODUCT NUMBER
 30001229 - 1 GAL - Green Cove Springs FL
 30001619 - 1 GAL - Columbus KS
 30001230 - 5 GAL - Green Cove Springs FL
 30001620 - 5 GAL - Columbus KS

USES

This tough material has multiple uses in new construction as well as maintenance and repair. Ideal for flashing construction and other detail roofing work such as tie-offs or shingle securement. Provides excellent waterproofing properties for temporary repairs or more permanent repairs when used with fiberglass mesh roof fabric.

APPLICATION

Apply with a trowel or knife. One gallon covers 12.5 sq. ft. when applied at 1/8" thickness.

PRODUCT DATA*

TYPICAL PHYSICAL PROPERTIES*

	MIN	MAX	METHOD
Total solids (non-volatile),%	75	85	D 4586
Volatiles, %	15	25	D 4586
Flash point, °F	100	- -	D 92
VOC, grams/litre	- -	300	
Asphalt, %	35	65	D 4

SPECIFICATION COMPLIANCE

ASTM D 4586 Type 1 Standard Specification for Asphalt Roof Cement.

ASTM D 3409 Standard Test Method for Adhesion of Asphalt-Roof Cement to Damp, Wet or Underwater Surfaces.

*All values stated as nominal

For Technical Services call 1-800-641-4691

Visit our Web Site at tamko.com



TAMKO
BUILDING PRODUCTS

TAMKO Logo, Roofer Logo and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

CAUTION: This product contains crystalline silica. Crystalline silica has been classified as a "known" human carcinogen by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains cutback asphalt. IARC has classified "extracts of steam and air-refined bitumens" (cutback asphalt) as "possibly carcinogenic to humans." The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing fumes and contact with skin.

Central District	220 West 4th St.	Joplin, MO	64801	800-641-4691
Northeast District	4500 Tamko Dr.	Frederick, MD	21701	800-368-2055
Southeast District	2300 35th St.	Tuscaloosa, AL	35401	800-228-2656
Southwest District	7910 S. Central Exp.	Dallas, TX	75216	800-443-1834
Western District	5300 East 43rd Ave.	Denver, CO	80216	800-530-8868

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.