

TAMKO BUILDING PRODUCTS, INC. SAFETY DATA SHEET – T03N2015

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: TAMKO Self Adhesive Rolled Roofing

LABEL: TAMKO SA Base

USE & DESCRIPTION: Self Adhesive Rolled Asphalt Roofing Products

CHEMICAL FAMILY: Mixture

MANUFACTURED BY:

TAMKO Building Products, Inc.

P. O. Box 1404

Joplin, MO 64802-1404

www.TAMKO.com

EMERGENCY TELEPHONE NUMBERS:

General Information: 1-417-624-6644 (8 a.m. - 5 p.m. CST)

Chemtrec: 1-800-424-9300 (24 HOURS)

2. HAZARDS IDENTIFICATIONSIGNAL WORD: **Warning**

GHS CLASSIFICATION:

Carcinogenicity – Category 2

Sensitization (Skin) – Category 1B

Skin Irritation – Category 2

Eye Irritation – Category 2B

**HAZARD STATEMENTS:**

Suspected of causing cancer.

Causes skin and eye irritation.

May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS:Prevention

Obtain special instructions before use.

Avoid breathing dust.

Wash hands and exposed skin thoroughly after handling.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

If on skin: Wash with plenty of water.

Get medical advice/attention: If exposed or concerned or you feel unwell, if eye and or skin irritation persists.

Specific treatment: See section 4-First Aid

In case of fire: See Section 5.

Take off contaminated clothing and wash before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

Store locked up.

Disposal

Dispose in accordance with Federal, State, and Local regulations. (See section 13 for additional information).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS No.	% by Weight
Asphalt	8052-42-4	60-80
Polymer	NE	10-18
Fiberglass Mat*	NE	5-8
*Contains Fiberglass	65997-17-3	4-7
*Urea Formaldehyde Binder	9011-05-6	0.5-1.5
*Formaldehyde	50-00-0	0.01-0.2

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of cool water for at least 20 minutes, occasionally lifting the eye lids to ensure thorough rinsing. Get medical attention if irritation persists.

SKIN CONTACT: Clean any exposed skin with warm soapy water if possible. If not, and a waterless hand cleaner is used, it should be without pumice. Do not use solvents or thinners to remove material from skin. Get medical attention if irritation persists or develops.

INGESTION: If swallowed, do not induce vomiting. If vomiting occurs, keep head lower than hips to avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis. Call poison control center or get immediate medical attention.

INHALATION: If inhalation of cured product particles, fumes, vapors, or mist occurs, remove person to fresh air. Drink water to clear throat or blow nose to clear. If not breathing, give artificial respiration or give oxygen by trained personnel and get immediate medical attention.

NOTES TO PHYSICIAN: Treatment should be based on removing the source of irritation with treatment of symptoms as necessary.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, CO₂, or foam fire extinguisher should be used. Avoid use of straight-stream water.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should not enter confined spaces without wearing a National Institute for Occupational Safety and Health (NIOSH) approved positive pressure self-contained breathing apparatus (SCBA) with full face mask and full protective equipment. Water may be used to cool containers in a fire-exposed area.

UNUSUAL FIRE OR EXPLOSION HAZARDS: When heated, fumes may burn if ignition source is provided. Petroleum asphalt fumes can explode if emitted in an enclosed environment and supplied with an ignition source. Burning product may cause thick black smoke.

SEE SECTION 10 FOR COMBUSTION PRODUCTS

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS IF MATERIAL IS SPILLED OR RELEASED: Pick up large pieces. Do not dry sweep dusts or blow with air in confined area.

WASTE DISPOSAL METHODS: Dispose in accordance with applicable Federal, State, and Local regulations. Do not burn.

7. HANDLING AND STORAGE

STORAGE TEMPERATURE: Store away from heat and all ignition sources and open flames in accordance with applicable laws and regulations.

THIS PRODUCT SHOULD NOT BE HEATED OR BURNED USING A DIRECT FLAME DEVICE.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Follow recommended work practices and use recommended personal protective clothing and equipment. See Section 8 of this SDS.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**EXPOSURE LIMITS**

Components Raw Products	CAS No.	OSHA		ACGIH		Unit
		TWA	STEL	TWA	STEL	
Asphalt	8052-42-4	NE	NE	0.5*	NE	mg/m ³
Fiberglass	65997-17-3	15/5**	NE	5***	NE	mg/m ³
Formaldehyde	50-00-0	0.75	2	NE	0.3	ppm

NE= Not established.

Note: Due to the form of the product, hazardous exposures from this product are not expected to occur. Gloves must be worn when handling and adequate ventilation must be provided during roofing related activities.

* Asphalt Fume as benzene-soluble inhalable aerosol (Bitumen); TWA for inhalable fraction.

** Total Nuisance Dust/Respirable Dust.

*** Inhalable Fraction.

RESPIRATORY PROTECTION: Normally not needed in well-ventilated areas. If applicable exposure standards are exceeded or can be exceeded, use a NIOSH approved air-purifying respirator. If concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator/SCBA use, fitting, training standards and regulations.

VENTILATION: Use only with adequate ventilation to maintain exposures below applicable exposure limits. Local exhaust ventilation and/or enclosure of the process may be required. All equipment must be explosion proof.

EYE PROTECTION: Chemical safety goggles with side-shields or face shield must be used if eye contact is possible.

SKIN: Chemical resistant gloves, apron, or other protective clothing needed to prevent skin contact. Must wear leather or heat-resistant gloves, long-sleeve cotton shirt, long pants with no cuffs, and non-skid shoes or boots with 6-inch leather uppers during application and/or tear off activities.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Asphalt coated mat.
Odor Threshold	Not Applicable
pH:	Not Applicable
Boiling Point:	>700 °F
Melting Point:	>200 °F
Flash Point:	Not Applicable
Autoignition Temperature:	> 460°C/860°F
Viscosity:	Not Applicable
Decomposition Temperature:	Not Applicable

Upper/Lower Flammability or Explosive Limits:	Not Applicable
Vapor Pressure:	Not Applicable
Vapor Density (Air = 1):	Not Applicable
Specific Gravity/Relative Density:	Variable
Solubility (IES):	No data available
Initial Boiling Point and Boiling Range:	Not Applicable
Evaporation Rate (Butyl Acetate = 1):	<0.1
Flammability(Solid and Gas):	Not Applicable
Partition Coefficient: N-Octanol/Water:	Not Applicable

10. STABILITY AND REACTIVITY

STABILITY: Stable

REACTIVITY: Will not occur.

CONDITIONS TO AVOID: Keep from heat, sparks, open flame and other sources of ignition. Avoid contact with strong oxidizing agents.

HAZARDOUS REACTION: Polymerization will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids or bases, oxidizing agents and selected amines.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons. These combustion products are not expected unless product is heated or burned.

11. TOXICOLOGICAL INFORMATION

EYE – Can cause eye irritation.

SKIN – Can cause skin irritation.

INHALATION – Dust may cause upper respiratory irritation.

INGESTION – May cause harmful effects if swallowed.

THE FOLLOWING COMPONENT DATA IS PROVIDED FOR USER INFORMATION:**FORMALDEHYDE**

Cancer - This product may contain formaldehyde. IARC and NTP have classified formaldehyde as a human carcinogen based on sufficient evidence that formaldehyde causes nasopharyngeal cancer in humans, limited evidence for cancer of the nasal cavity and paranasal sinuses, and "strong but not sufficient evidence" for leukemia. The finding for leukemia reflects the epidemiologists' finding of strong evidence in human studies coupled with an inability to identify a mechanism for induction of leukemia. The physical nature of this product may help limit any inhalation hazard from formaldehyde during application and in its hardened state.

Acute Effects - The major acute toxic effects caused by formaldehyde exposure via inhalation are eye, nose, and throat irritation and effects on the nasal cavity. Other effects seen from exposure to high levels of formaldehyde in humans are coughing, wheezing, chest pains, and bronchitis. Ingestion exposure to formaldehyde in humans has resulted in corrosion of the gastrointestinal tract and inflammation and ulceration of the mouth, esophagus, and stomach.

Chronic Effects - In addition to cancer, exposure to formaldehyde by inhalation in humans has been associated with respiratory symptoms and eye, nose, and throat irritation. Repeated contact with liquid solutions of formaldehyde has resulted in skin irritation and allergic contact dermatitis in humans.

ASPHALT

Cancer - This product contains cutback asphalt. In 1987 IARC classified "extracts of steam and air- refined bitumens" (cutback asphalt) as Group 2B, "possibly carcinogenic to humans." In 2011 IARC did not specifically classify cutback asphalt as Group 2B. NIOSH has also concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. Asphalt may also cause irritation of the respiratory tract. The physical nature of this product may help limit any inhalation hazard from asphalt after curing. However, physical forces such as sawing, grinding, drilling and other demolition work on this product may liberate cured product particles containing asphalt. Burning or heating of the product may cause fumes, vapors or mists.

Acute Effects - Inhalation of cured product particles, fumes, vapors, or mist may cause nose, throat, and mucous membrane irritation. Eye contact may cause severe irritation, redness, tearing, and blurred vision. If ingested, may cause mouth, throat and gastrointestinal tract irritation and upset with possible nausea, vomiting and diarrhea.

Chronic Effects - In addition to cancer, prolonged or repeated skin contact may result in dryness and irritation of the skin. Long term skin exposure to asphalt can increase sensitivity to the sun, and may cause discoloration. Asphalt may also cause irritation of the respiratory tract.

12. ECOLOGICAL INFORMATION

Ecotoxicity – No data available

Persistence and degradability – No data available

Bioaccumulative potential – No data available

Mobility in Soil – No data available

Other adverse effects (GHG, Ozone) - No data available

13. DISPOSAL CONSIDERATIONS

This product has not been regulated as a hazardous waste by the USEPA. Dispose in accordance with Federal, State, and Local regulations.

14. TRANSPORT INFORMATION

This product is not regulated as a hazardous material for transport under 49 CFR or for vessel transport under the IMDG Code.

DOT PROPER SHIPPING NAME: Not Applicable

DOT HAZARD CLASSIFICATION: Not Applicable

DOT LABELING REQUIREMENTS: Not Applicable

UN/NA NUMBER: Not Applicable

PACKING GROUP: Not Applicable

IMDG CODE: Not Applicable

IMDG SHIPPING NAME: Not Applicable

IMDG HAZARD CLASS: Not Applicable

UN/ID NUMBER: Not Applicable

PACKING GROUP NUMBER: Not Applicable

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA): Some components in this product are listed on the TSCA Inventory.


COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA): None

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA), TITLE III:

Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazard Categories: Immediate Health; Delayed Health; Fire Hazard

Section 313 Reportable Ingredients: None

California Proposition 65:  **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov/product.

16. OTHER INFORMATION

<u>HMS Rating:</u>	<u>NFPA Rating:</u>
Health - * 1	Health - 1
Flammability - 1	Flammability - 1
Reactivity - 0	Reactivity - 0

Preparation Date: **April 2015**Revision Date: **February 2017**

Revisions: Corrected typos in Sections 3 and 7
Updated table footnotes in Section 8
Updated California Proposition 65 warning language in Section 15

Disclaimer of Liability

The information and recommendations contained herein are to the best of **TAMKO Building Products, Inc.**'s knowledge and belief, accurate and reliable as of the date issued. **TAMKO Building Products, Inc.** does not warrant or guarantee their accuracy or reliability, and **TAMKO Building Products, Inc.** shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy his or herself that they are suitable and complete for the user's particular use.