



TECHNICAL NOTICE

August 28, 2019

ALTERNATIVE VALLEY APPLICATION INSTRUCTIONS FOR HERITAGE® LAMINATED SHINGLES MANUFACTURED AT TUSCALOOSA, AL*

The information below provides an alternative to the Valley Application section of the *Application Instructions for Heritage® Laminated Asphalt Shingles (Tuscaloosa, AL)*:

Over the shingle underlayment previously installed in the field of the roof and extended through the valley, center in the valley a minimum 36 in. wide sheet of TAMKO® Moisture Guard, TW Metal and Tile Underlayment, any self-adhesive underlayment designed for use with asphalt shingles which meets ASTM D1970, or a minimum 50 lb. roll roofing. Nail the underlayment only where necessary to hold it in place and then only nail the outside edges.

Follow the remainder of the instructions in the Valley Application section of the *Application Instructions for Heritage® Laminated Asphalt Shingles (Tuscaloosa, AL)*.

Except as set forth herein, this Technical Notice is not intended to alter the Application Instructions for TAMKO fiberglass/asphalt shingles, which are available at TAMKO.com and are printed on the wrapper of each bundle of shingles. This Technical Notice is not intended, nor should it be construed to, alter or waive any portion of the *TAMKO Fiberglass/Asphalt Shingle Limited Warranty and Arbitration Agreement*.

Additional information about TAMKO products is available at tamko.com.

* To obtain the current version of this Technical Notice and the most recent limited warranty, visit TAMKO's website at tamko.com. TAMKO reserves the right to update, remove, or otherwise modify any Technical Notice. If a previous Technical Notice currently is not listed at tamko.com then it is no longer valid and should not be referenced or relied upon for any reason.

©2019 TAMKO Building Products LLC. TAMKO, TAMKO logo and Heritage are registered trademarks of TAMKO Building Products LLC.