



TECHNICAL NOTICE

August 28, 2019

INSTALLATION OF TAMKO FIBERGLASS/ASPHALT SHINGLES OVER ORIENTED STRAND BOARD

TAMKO® shingles are for application to roof decks consisting of plywood, oriented strand board (OSB) or sheathing boards capable of receiving and retaining fasteners. TAMKO accepts installation of TAMKO Fiberglass/Asphalt shingles over oriented strand board (OSB) that meets the following requirements:

ORIENTED STRAND BOARD: Oriented strand board shall be exterior grade as defined by APA – The Engineered Wood Association, minimum 7/16 in. thickness, APA-rated in accordance with Voluntary Standard PS 2 and applied in accordance with the recommendations of APA – The Engineered Wood Association.

Except as set forth herein, this Technical Notice is not intended to alter the Application Instructions for TAMKO fiberglass/asphalt shingles, which are available at TAMKO.com and are printed on the wrapper of each bundle of shingles. This Technical Notice is not intended, nor should it be construed to, alter or waive any portion of the *TAMKO Fiberglass/Asphalt Shingle Limited Warranty and Arbitration Agreement*.

Additional information about TAMKO products is available at tamko.com.

* To obtain the current version of this Technical Notice and the most recent limited warranty, visit TAMKO's website at tamko.com. TAMKO reserves the right to update, remove, or otherwise modify any Technical Notice. If a previous Technical Notice currently is not listed at tamko.com then it is no longer valid and should not be referenced or relied upon for any reason.

©2019 TAMKO Building Products LLC. TAMKO and TAMKO logo are registered trademarks of TAMKO Building Products LLC.